



## edge<sup>®</sup>pH–Innovation dedicated to a single parameter

edge pH's groundbreaking design is the culmination of Hanna's vision, design capabilities, integrated production, and world class R&D. edge pH is a single meter that can measure pH and ORP and is incredibly easy to use.

- Resolution selectable from 0.01 and 0.001 pH
- Range -2.000 to 16.000 pH
- Accuracy  $\pm 0.002$  pH for 0.001 pH resolution;  $\pm 0.01$  for 0.01 resolution
- Data logging
  - Manual log-on-demand
  - Manual log-on-stability
  - Interval logging
- Temperature readout ( $^{\circ}\text{C}$  or  $^{\circ}\text{F}$ )
- Automatic Temperature Compensation (ATC)
- CAL Check<sup>™</sup> Indicators:
  - Probe condition
  - Response time
  - Check buffer
  - Clean electrode
- Sensor Check<sup>™</sup> Indicators:
  - Broken electrode
  - Clogged junction
- GLP data
  - Records date, time, offset, slope, and buffers used during calibration
- Five-point calibration
  - A choice of seven pre-programmed buffers plus two selectable custom buffers
- Calibration tag on screen
  - Identifies buffers used for current calibration
- Calibration expiration warning

## edge® pH technical features

### Rechargeable Battery

edge pH has a built in rechargeable battery that is charged when the meter is plugged into benchtop or wall mount cradle. The battery can also be recharged through the micro USB port from a computer or the power supply.



### Two USB ports

edge pH includes one standard USB for exporting data to a flash drive, and one micro USB port for exporting files to your computer as well as for charging when the cradle is not available.



### Clear, full text readout

edge pH features clear, full text guides displayed on the bottom of the screen. There is no need to decipher scrambled abbreviations or symbols; these helpful messages guide you through every process quickly and easily.



### Data logging

edge pH allows you to store up to 1000 log records of data. Data sets include readings, GLP data, date, and time.



### GLP

Data of the last calibration you perform is stored in the sensor including the date, time, and buffers used. When the sensor is connected to edge pH, GLP data is automatically transferred.

### Two Operating Modes

edge pH can be used in Extended or Basic Operating Modes. Extended Mode enables all edge features while Basic Mode reduces features—ideal for routine measurements by displaying a simplified screen and features.



### CAL Check™

Hanna's exclusive CAL Check feature analyzes the pH electrode response in the pH buffers during the calibration process to alert the user of potential problems such as a contaminated buffer or dirty electrode. After calibration, indicators for probe condition are displayed on the measurement screen. The probe condition is based on offset and slope characteristics of the pH electrode.

### Sensor Check™

When used with Hanna's electrodes equipped with a matching pin, edge constantly checks the impedance of the pH measuring electrode to notify you in real time in the event of glass breakage. During calibration, Sensor Check checks the state of the junction. The reference junction is also evaluated and reported on the display.

### ORP Measurement

edge pH measures ORP with edge compatible ORP probes.

## edge pH design features



### Capacitive touch keypad

edge pH features sensitive capacitive touch buttons for accurate keystrokes when navigating edge's menus and screens. Since they are part of the screen, the buttons can never get clogged with sample residue.



### Easy to read LCD

edge pH features a 5.5" (14 cm) LCD display that you can clearly view from over 5 m (16.4'). The large display, with its wide 150° viewing angle, provides one of the easiest to read LCDs in the industry.



### Zero footprint

Using the wall mount cradle (included), edge pH can be placed on a wall, leaving zero footprint on the benchtop space. The cradle has a built-in connector to power and charge the batteries.



## A hybrid meter that can be used in portable, wall-mount, and benchtop configurations

The versatile design of edge®pH enables it to be used as a portable, wall-mount, or benchtop meter. edge pH simplifies measurement, configuration, calibration, diagnostics, logging and transferring data directly to a computer or USB drive.



### Portable field unit

edge pH is ideal for field use due to its light weight, large screen, and thin design. It can easily be slipped into a backpack or messenger bag. The battery life lasts up to 8 hours when used as a portable device.



### Wall-mount cradle

The included wall-mount cradle makes it easy to conserve space on the benchtop while also charging edge pH with the AC adapter. The cradle is ideal for continuous monitoring applications.



### Electrode holder with built-in cradle

The electrode holder features a swivel, adjustable arm with a built-in cradle to hold edge pH securely in place at the optimum viewing angle.



### 3.5 mm probe input

Plugging an electrode in has never been simpler; no alignments or broken pins, simply connect the 3.5 mm plug and begin. Digital electrodes are automatically recognized.

### Sleek design

Incredibly thin and lightweight, edge® pH measures just 1/2" (12 mm) thick and weighs just 8.8 ounces (250 g).



### Specifications

|   |                           |   |
|---|---------------------------|---|
| pH  | Range*                    | -2.00 to 16.00 pH; -2.000 to 16.000 pH <sup>†</sup>   |
|   | Resolution                | 0.01 pH; 0.001 pH <sup>†</sup>  |
|   | Accuracy (@25°C/77°F)     | ±0.01 pH; ±0.002 pH <sup>†</sup>  |
|   | Calibration               | automatic, up to three points (five points <sup>†</sup> ) calibration, 5 standard (7 standard <sup>†</sup> ) buffers available (1.68 <sup>†</sup> , 4.01 or 3.00, 6.86, 7.01, 9.18, 10.01, 12.45 <sup>†</sup> ) and two custom buffers <sup>†</sup> |
|   | Temperature Compensation* | automatic, -5.0 to 100.0°C (23.0 to 212.0°F) (using built-in temperature sensor)  |
| mV pH   | Electrode Diagnostics     | standard mode: probe condition, response time and out of calibration range  |
|   | Range                     | ±1000 mV  |
|   | Resolution                | 0.1 mV  |
| ORP   | Accuracy (@25°C/77°F)     | ±0.2 mV   |
|   | Range                     | ±2000 mV  |
|   | Resolution                | 0.1 mV  |
| Temperature   | Accuracy (@25°C/77°F)     | ±0.2 mV (±999.9 mV); ±1 mV (±2000 mV)   |
|   | Calibration               | one-point calibration   |
|   | Range*                    | -20.0 to 120.0°C; -4.0 to 248.0°F   |
| Additional Specifications   | Resolution                | 0.1°C; 0.1°F  |
|   | Accuracy                  | ±0.5°C; ±0.9°F  |
|   | Probe                     | HI11310 digital glass body pH electrode with 3.5 mm (1/8") connector and 1 m (3.3') cable   |
|   | Logging                   | up to 1000 <sup>†</sup> (400 for basic mode) records organized in: manual log-on-demand (max. 200 logs), manual log-on-stability (max. 200 logs), interval logging <sup>†</sup> (max. 600 samples; 100 lots)  |
|   | Connectivity              | 1 USB port for storage; 1 micro USB port for charging and PC connectivity   |
|   | Environment               | 0 to 50°C (32 to 122°F); RH max 95% non-condensing  |
| Ordering Information  | Power Supply              | 5 VDC adapter (included)  |
|   | Dimensions                | 202 x 140 x 12 mm (7.9" x 5.5" x 0.5")  |
|   | Weight                    | 250 g (8.82 oz.)  |
| <p><b>HI2002-01</b> (USA plug) and <b>HI2002-02</b> (European plug) edge pH includes: HI11310 glass body, refillable pH electrode, pH 4 buffer solution sachets (4), pH 7 buffer solution sachets (2), pH 10 buffer solution sachets (2), electrode cleaning solution sachets (2), benchtop docking station with electrode holder, wall-mount cradle, USB cable, 5 VDC power adapter, quality certificates, and instruction manual.</p> <p><b>HI2002-03</b> includes the above without electrode.</p> |                           |   |

\* limits will be reduced to actual probe limits  
<sup>†</sup> standard mode only